



Applications

The QCI200 series interconnected levers are designed for multifamily, assisted living, commercial & mixed use applications where single motion egress is required. These leversets deliver premium performance and are designed to withstand the physical abuses of the applied environment.

Performance Features

- Tested to exceed 400,000 cycles for Grade 2 certification.
- Single motion egress provides easy emergency exit.
- Full 1" (25mm) throwbolt with saw resistant hardened steel roller pin.
- Anti-drill design deadbolt— two (2) ball bearings inserted to prevent drill attacks.
- ADA thumbturn.

Certifications



- ANSI/BHMA A156.12 - 1999 Grade 2
- UL/cUL listed (3-hours) for "A" label single door applications (4'x 8') (1.219m x 2.438m)
- UL10C / UBC 7-2 (1997) Positive Pressure Rated
- UL10B Pressure Rated
- ADA Compliant ANSI A117.1 Accessibility Code

Product Specifications

- Door Range – 1 3/8" - 1 3/4" (35mm - 44.5mm)
- 4" Center to Center
- Backset – 2 3/4" (70mm) standard. 2 5/8" (60mm) available.
- Exposed Trim – Wrought brass or bronze with cast zinc lever.
- Strikes – "T" strike 1 1/8" x 2 3/4" standard for lever, deadbolt strike 1 1/8" x 2 3/4" standard. Other strike options also available.
- Latchbolt – Keyed 1/2" (13mm) Steel Throw with auxillary latch, passage 1/2" (13mm) spring latch.
- Handing – All QC I200 locksets are non-handed.
- Standard door prep: 2 1/8" Cross Bore (54mm)
- Latch Hole: 1" Diameter Edge Bore
- Rose Diameter: 2 1/2" (63mm)
- Inside Escutcheon 3" x 8" (76mm x 203mm);
Optional Exterior Escutcheon 3 1/4" x 8" (82.5mm x 203mm)

Keying

- 6-pin brass cylinders. Many keying options available from our factory to include, but not limited to, master keying, grandmaster keying and construction keying. Small Format Interchangeable Core cylinder also available.
- 2 Keys per lockset
- Offered with the following keyway options: KW-Kwikset, WE-Weiser, SC-Schlage, GA-Yale, LA-Sargent, BF-Best "F" & LC-Less Cylinder.

Warranty

Lifetime Mechanical & 3 year finish*
*(613/US10B carries no finish warranty)



Pinnacle - Single Locking



Pearce - Double Locking

Functions

ANSI	K2	Description
F95	QCI230	Single Locking (Passage Lever)
F95	QCI231	Single Locking SFIC (Passage Lever)
F97	QCI250	Double Locking (Entry Lever)
F97	QCI251	Double Locking SFIC (Entry Lever)

Finishes

BHMA	US	Description
605	US3	Bright Brass
613	US10B	Oil Rubbed Bronze
619	US15	Satin Nickel
626	US26D	Satin Chrome